

# INSULTEC AUSTRALIA PTY LIMITED

ABN 93 092 861 008



Manufacturing Site: U1/481 Victoria Street, Wetherill Park, NSW 2164 Australia  
Registered Office Address: 10 Pacific Highway, Calga, NSW 2250 Australia

Tel: +61 (0)2 4375 1023 Fax: (02) 4375 1053  
Email: [insultecaustralia@bigpond.com](mailto:insultecaustralia@bigpond.com)  
Website: [www.insultecaustralia.com.au](http://www.insultecaustralia.com.au)

## **PRODUCT DATA SHEET** **ASBESTOS SEALER**

- Fibro asbestos sealer and conditioner
- Outstanding penetration into fibro asbestos
- Excellent binding properties
- Excellent ability to kill mould and fungus

### **COMPOSITION**

Asbestos sealer is 100% Acrylic resin with anti mould and fungus agents.

### **RECOMMENDED USES**

Asbestos sealer is formulated for exterior application on fibro asbestos. It is typically used as a single coat over prepared asbestos surfaces. It encapsulates the loose asbestos.

### **APPLICATION DATA**

#### **Fibro Asbestos:**

Remove as much destroyed mould and fungus as possible then spray on at low pressure to create a flood coat at approximately 4 to 6 square meters per litre.

#### **Brush / Roller:**

Stir thoroughly before use. Apply directly from the container at a supplied viscosity.

#### **Airless Spray:**

Suitable for diaphragm spray units. Spray at low pressure and flood coat the surface.

### **COVERAGE**

4-6 sq.metre per 1 litre

### **SAFETY PRECAUTIONS**

Provide adequate ventilation during use. When spray painting, applicators should comply with the provisions of the relevant spray-painting regulations.

Avoid contact with skin and eyes. Wear protective goggles and gloves when handling the material. In the case of skin contact, remove contaminated clothing and clean skin with white spirit then wash skin thoroughly with soap and water. Seek medical attention if eyes are affected by splash.

### **GENERAL**

Rate of drying is affected by airflow, temperature and relative humidity. Do not paint if rain is imminent or 85% etc.

### **PACKAGING AND TRANSPORTATION**

Available in 20 litre or 1000 litre containers.

### **DISCLAIMER**

The data contained herein is based upon information, which the company believed to be reliable at the time of preparation of this data sheet. No responsibility can be accepted or any express or implied warranty given where performance of the product is affected by surface method of application, or any other circumstances beyond the control of the company.

July 2012